

COLORJET DELIVERS IMPECCABLE PRINT RESULTS & FLAWLESS SERVICE ACROSS THE WORLD

c:

AMAZINGLY HIGH PRODUCTIONS, SURPRISINGLY LOW CAPITAL COSTS

- Best in class for outdoors & indoors signage
- High quality prints at blazing speed
- Consistent jetting using AIVC technology
- Automatic bulk ink supply system
- USB high speed Interface for faster data transfer

• Value for money, saves ink and time



COLORJET GROUP

INDIA: B-195, Phase-II, Noida-201305 (U.P.), INDIA. T+91 120 4548195

DUBAI: Block-A, Office No: 115, Hamsah Building, Karama, P.O. Box: 123360, Dubai-UAE. T 00971 43961744

sales@colorjetgroup.com | www.colorjetgroup.com

Accessories shown along with different printers in this brochure are not part of standard equipment. The final results of ColorJet are purely indicative and non-binding. Alterations and amendments can occur in specifications, materials or accessories without prior notice. Periodic maintenance is important for best quality output. ColorJet shall not be liable for any specific or consequential damages that result from the use of, or the inability to use, the materials or the performance of the products. All trademarks logic symbols and designs depicted / mentioned in this brochure are trademarks and congrights of their respective brand owners.







		IRISJET	
Printing Technology		Drop-on-demand, Piezo Electric Inkjet	
Print Heads		Industrial Grade Jetting Assemblies	
Media	Width	3300 mm (129 in)	
	Thickness	Maximum 3.0 mm (120 mil) with liner (flexible)	
	Roll Outer Diameter	Maximum 300 mm (12 in), 50.8 (2 in)	
	Roll Weight	Maximum 90 kg	
	Core Diameter	76.2 mm (3 in)	
	Туре	SAV, PVC Banner, Backlit Film, Window Film, Fabric (Solvent Base)	
Printing Width		Maximum 3200 mm (126 in)	
Inks	Туре	Solvent/Mild Solvent Inks	
	Colors	4 Colors (CMYK)	
Printing Resolution (dots per inch)		Maximum 1440 dpi	
Distance Accuracy		Error of less than ±0.3 % of distance traveled, or ±0.3 mm, whichever is greater	
Media Heating System		Print heater and pre-heater, setting range for the preset temperature 30 to 60°C. Dryer setting range for the preset temperature: 30 to 60°	
Connectivity		High Speed USB	
Power Requirements		AC 220 V ±10%, 15 A, 50/60 Hz	
Dimension		4500 x 1000 x 1400 mm (WxDxH)	
Weight (approx. with stand)		300 Kgs	
Environmental	Power ON	Temperature: 18 to 28°C Hmidity: 20 to 80%RH (Non-condensing)	
	Power OFF	Temperature: 5 to 40°C Humidity: 20 to 80%RH (Non-condensing)	
Printer Model	IJ4012	IJ8012	IJ4024
Draft Mode	42 sqm/hr (452 sq. ft/hr)	70 sqm/hr (753 sq. ft/hr)	85 sqm/hr (915 sq. ft/hr)
Production Mode	28 sqm/hr (300 sq. ft/hr)	55 sqm/hr (592 sq. ft/hr)	65 sqm/hr (700 sq. ft/hr)
Quality Mode	24 sqm/hr (259 sq. ft/hr)	40 sqm/hr (430 sq. ft/hr)	49 sqm/hr (527 sq. ft/hr)